

## CLAIMS

What is claimed is:

- 5           1. A holding device for holding a portable object, the holding device comprising:
- a support platform;
- a first arm coupled to the support platform;
- a second arm coupled to the support platform;
- a biasing member located between the first and second arms;
- 10           a locking mechanism capable of maintaining the first arm and the second arm in any
- one of a plurality of discrete positions with respect to each other; and
- a release button adjacent to the support platform, the release button capable of
- releasing the locking mechanism,
- wherein:
- 15           the biasing member is capable of urging at least a portion of the first arm and at
- least a portion of the second arm toward each other.
2. The holding device of claim 1 further comprising:
- a first grip coupled to the first arm; and
- 20           a second grip coupled to the second arm.
3. The holding device of claim 1 wherein:
- the first arm comprises a first arm axis;

the second arm comprises a second arm axis;

the first arm axis and the second arm axis are substantially perpendicular to the support platform;

the first arm is capable of rotating about the first arm axis; and

5 the second arm is capable of rotating about the second arm axis.

4. The holding device of claim 1 wherein:

the biasing member comprises a spring.

10 5. The holding device of claim 1 wherein:

the support platform comprises an upper surface and a lower surface substantially opposite the upper surface; and

the release button is located at the upper surface of the support platform.

15 6. The holding device of claim 5 wherein:

the release button protrudes from the support platform.

7. The holding device of claim 5 wherein:

the lower surface of the support platform is coupled to a mounting mechanism.

20

8. The holding device of claim 1 wherein:

the locking mechanism comprises:

a ratchet; and

a pawl capable of engaging the ratchet.

9. The holding device of claim 8 wherein:

the ratchet is integral with one of the first and second arms.

5

10. The holding device of claim 8 wherein:

the ratchet comprises a plurality of teeth and a plurality of indentations;

the pawl is capable of engaging at least one of the plurality of indentations; and

the first arm and the second arm are held in a fixed position with respect to each other

10

when the pawl is engaged with one of the plurality of indentations.

11. The holding device of claim 1 wherein:

the first arm further comprises a first plurality of teeth;

the second arm further comprises a second plurality of teeth; and

15

the first plurality of teeth interacts with the second plurality of teeth such that a movement of one of the first and second arms causes a movement in the other of the first and second arms.

12. The holding device of claim 1 further comprising:

20

a pad over the release button.

13. The holding device of claim 1 wherein:

the first grip and the second grip comprise:

a substantially rigid core; and

a flexible material located adjacent to the core.

14. The holding device of claim 13 wherein:

5

the core is formed from a rigid plastic material; and

the flexible material comprises a thermoplastic elastomer.

15. A holding device for holding a portable object, the holding device comprising:

a support platform having an upper surface for supporting the portable object and a lower surface substantially opposite the upper surface, the upper surface having a release button thereon;

5 a first lever coupled to the support platform;

a second lever coupled to the support platform;

a first grip coupled to a first portion of the first lever;

a second grip coupled to a first portion of the second lever;

a first handle coupled to a second portion of the first lever;

10 a second handle coupled to a second portion of the second lever;

a spring coupled between second portions of the first and second levers; and

a locking mechanism capable of maintaining the first lever and the second lever in any one of a plurality of discrete positions with respect to each other,

wherein:

15 the spring is capable of urging the first grip and the second grip toward each other;

the release button is capable of being activated by the application of a force to the portable object when the portable object is supported by the upper surface and located between the first and second grips; and

20 the release button is capable of releasing the locking mechanism.

16. The holding device of claim 15 wherein:

the first arm comprises a first axis of rotation located between the first and second portions of the first arm;

the second arm comprises a second axis of rotation located between the first and second portions of the second arm;

5 the first arm axis and the second arm axis are substantially perpendicular to the upper surface of the support platform;

the first arm is capable of rotating about the first arm axis; and

the second arm is capable of rotating about the second arm axis.

10 17. The holding device of claim 15 wherein:

the release button protrudes from the support platform.

18. The holding device of claim 15 wherein:

the lower surface of the support platform is coupled to a mounting mechanism.

15 19. The holding device of claim 15 wherein:

the locking mechanism comprises:

a ratchet; and

a pawl capable of engaging the ratchet.

20 20. The holding device of claim 19 wherein:

the ratchet is integral with one of the first and second arms.

21. The holding device of claim 20 wherein:

the ratchet comprises a plurality of teeth and a plurality of indentations;

the pawl is capable of engaging at least one of the plurality of indentations; and

the first arm and the second arm are held in a fixed position with respect to each other

when the pawl is engaged with one of the plurality of indentations.

22. The holding device of claim 21 wherein:

the first arm further comprises a first plurality of teeth at the second portion of the first arm;

the second arm further comprises a second plurality of teeth at the second portion of the second arm; and

the first plurality of teeth interacts with the second plurality of teeth such that a movement of one of the first and second arms causes a movement in the other of the first and second arms.

23. The holding device of claim 15 further comprising:

a pad over the release button.

24. The holding device of claim 23 wherein:

the first grip and the second grip comprise:

a substantially rigid core; and

a flexible material located adjacent to the core.

25. The holding device of claim 24 wherein:

the core is formed from a rigid plastic material; and

the flexible material comprises a thermoplastic elastomer.



26. A method of manufacturing a holding device for a portable object, the method comprising:

providing a support platform having a first arm and a second arm coupled thereto;

providing a biasing member capable of urging at least a portion of the first arm and at least a portion of the second arm toward each other, the biasing member located between the first arm and the second arm;

providing a locking mechanism capable of maintaining the first arm and the second arm in any one of a plurality of discrete positions with respect to each other; and

providing a release button adjacent to the support platform, the release button capable of releasing the locking mechanism.

27. The method of claim 26 further comprising:

providing a first grip coupled to the first arm; and

providing a second grip coupled to the second arm.

28. The method of claim 26 further comprising:

providing the first arm to be rotatable about a first arm axis; and

providing the second arm to be rotatable about a second arm axis,

wherein:

the first arm axis and the second arm axis are substantially perpendicular to the support platform.

29. The method of claim 26 further comprising:

providing the locking mechanism to comprise:

a ratchet; and

a pawl capable of engaging the ratchet.